

OSHA HazCom Standard 29 CFR 1910.1200(g) revised in 2012 and GHS Rev 03.

Issue date 07/30/2021 Reviewed on 07/30/2021

## 1 Identification

- · Product Identifier
- · Trade Name: MagReSyn® Hydroxyl
- Product Number:

MR-HYX002 (2 ml); MR-HYX005 (5 ml); MR-HYX010 (2 x 5 ml) MR-HYX050 (50 ml); MR-HYX100 (100 ml); MR-HYX400 (400 ml)

- · Relevant identified uses of the substance or mixture and uses advised against:
- · Product Description: Magnetic microparticles for protein binding
- Application of the substance / the mixture:

Magnetic microspheres suspended in an aqueous solution with ethanol. The product is intended for biomolecule or chemical ligand immobilization for a variety of subsequent end-user applications in research and development. This product is for research and development use only.

Uses advised against

It is not intended for any animal or human therapeutic or diagnostic use unless otherwise stated.

- · Details of the Supplier of the Safety Data Sheet:
- · Manufacturer/Supplier:

ReSyn Biosciences Pty Ltd

Building 20

**CSIR** 

Meiring Naude Road

Brummeria

Pretoria

South Africa

0184

- +27128414153
- · Emergency telephone number: +27128414153

#### 2 Hazard(s) Identification

· Classification of the substance or mixture:



Flame

Flam. Liq. 2 H225 Highly flammable liquid and vapor.



Eye Irrit. 2A H319 Causes serious eye irritation.

STOT SE 3 H335 May cause respiratory irritation.

- · Label elements:
- Hazard pictograms:





- · Signal word: Danger
- Hazard-determining components of labeling:

Ethanol

· Hazard statements:

H225 Highly flammable liquid and vapor.



OSHA HazCom Standard 29 CFR 1910.1200(g) revised in 2012 and GHS Rev 03.

Issue date 07/30/2021 Reviewed on 07/30/2021

## Trade Name: MagReSyn® Hydroxyl

H319 Causes serious eye irritation.

H335 May cause respiratory irritation.

#### Precautionary statements:

P210 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

P240 Ground/bond container and receiving equipment.

P241 Use explosion-proof electrical/ventilating/lighting/equipment.

Use only non-sparking tools. P242

P243 Take precautionary measures against static discharge. P261 Avoid breathing dust/fume/gas/mist/vapors/spray.

P264 Wash thoroughly after handling.

Use only outdoors or in a well-ventilated area. P271

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P303+P361+P353 If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/

shower.

P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing.

Call a poison center/doctor if you feel unwell. P312

If eye irritation persists: Get medical advice/attention. P337+P313

P370+P378 In case of fire: Use CO2, powder or water spray to extinguish. P403+P233 Store in a well-ventilated place. Keep container tightly closed.

P403+P235 Store in a well-ventilated place. Keep cool.

Store locked up. P405

P501 Dispose of contents/container in accordance with local/regional/national/international

regulations.

#### · Unknown acute toxicity:

This value refers to knowledge of known, established toxicological or ecotoxicological values. 0 % of the mixture consists of component(s) of unknown toxicity.

· Classification system: NFPA/HMIS Definitions: 0-Least, 1-Slight, 2-Moderate, 3-High, 4-Extreme

· NFPA ratings (scale 0 - 4)



Health = 2 Fire = 3Reactivity = 0

## · HMIS-ratings (scale 0 - 4)



Health = 2 Fire = 3

· Hazard(s) not otherwise classified (HNOC): None known

## Composition/Information on Ingredients

#### · Chemical characterization: Substance

2% MagReSvn® Hydroxyl microparticles

Polymer coated microparticles: (20 mg per ml, no CAS number, consists of 60% magnetite and 40% polymer, polymer is a polyethyleneimine derivative)

Description: Mixture of substances listed below with non-hazardous additions.

## Dangerous Components:

CAS: 64-17-5 Ethanol Flam. Lig. 2, H225; (1) Eye Irrit. 2A, H319; STOT SE 3, H335 RTECS: KQ 6300000

(Contd. on page 3)

15-35%



OSHA HazCom Standard 29 CFR 1910.1200(g) revised in 2012 and GHS Rev 03.

Issue date 07/30/2021 Reviewed on 07/30/2021

#### Trade Name: MagReSyn® Hydroxyl

#### · Additional information:

The exact percentages of the ingredients of this mixture are considered to be proprietary and are withheld in accordance with the provisions of paragraph (i) of §1910.1200 of 29 CFR 1910.1200 Trade Secrets.

### 4 First-Aid Measures

- · Description of first aid measures
- · After inhalation: In case of unconsciousness place patient stably in the side position for transportation.
- · After skin contact:

Immediately wash with water and soap and rinse thoroughly.

If skin irritation occurs, consult a doctor.

· After eve contact:

Rinse opened eye for at least 15 minutes under running water. If symptoms persist, consult a doctor.

If easy to do so, remove contact lenses if worn.

If eye irritation occurs, consult a doctor.

- · After swallowing: If swallowed and symptoms occur, consult a doctor.
- · Information for doctor
- · Most important symptoms and effects, both acute and delayed: No further relevant information available.
- Indication of any immediate medical attention and special treatment needed:

No further relevant information available.

## 5 Fire-Fighting Measures

- · Extinguishing media
- · Suitable extinguishing agents: CO2, sand, extinguishing powder. Do not use water.
- · For safety reasons unsuitable extinguishing agents: Water with full jet
- · Special hazards arising from the substance or mixture: No further relevant information available.
- Advice for firefighters
- · Special protective equipment for firefighters:

As in any fire, wear self-contained breathing apparatus pressure-demand (NIOSH approved or equivalent) and full protective gear to prevent contact with skin and eyes.

## 6 Accidental Release Measures

### · Personal precautions, protective equipment and emergency procedures:

Wear protective equipment. Keep unprotected persons away.

Methods and material for containment and cleaning up:

Absorb with liquid-binding material (i.e. sand, diatomite, acid binders, universal binders, sawdust).

Ensure adequate ventilation.

Do not flush with water or aqueous cleansing agents

Dispose of the collected material according to regulations.

· Reference to other sections:

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

· PAC-1:	
64-17-5 Ethanol	1,800 ppm
· PAC-2:	
64-17-5 Ethanol	3300* ppm
· PAC-3:	
64-17-5 Ethanol	15000* ppm
	(Contd. on page 4)

(Contd. on page 4)



OSHA HazCom Standard 29 CFR 1910.1200(g) revised in 2012 and GHS Rev 03.

Issue date 07/30/2021 Reviewed on 07/30/2021

Trade Name: MagReSyn® Hydroxyl

## 7 Handling and Storage

- · Handling
- · Precautions for safe handling:

Ensure good ventilation/exhaustion at the workplace.

Prevent formation of aerosols.

· Information about protection against explosions and fires:

Keep ignition sources away - Do not smoke.

Protect from heat.

Protect against electrostatic charges.

- · Conditions for safe storage, including any incompatibilities
- · Storage
- Requirements to be met by storerooms and receptacles: Store in a cool location.
- · Information about storage in one common storage facility: Not required.
- Further information about storage conditions:

Keep receptacle tightly sealed.

Store in cool, dry conditions in well sealed receptacles.

Protect from heat and direct sunlight.

· Specific end use(s): No further relevant information available.

## 8 Exposure Controls/Personal Protection

- · Additional information about design of technical systems: No further data; see section 7.
- · Control parameters:

### · Components with occupational exposure limits:

#### 64-17-5 Ethanol

PEL Long-term value: 1900 mg/m³, 1000 ppm REL Long-term value: 1900 mg/m³, 1000 ppm TLV Short-term value: 1880 mg/m³, 1000 ppm

- · Additional information: The lists that were valid during the creation of this SDS were used as basis.
- · Exposure controls:
- · Personal protective equipment
- · General protective and hygienic measures:

The usual precautionary measures for handling chemicals should be followed.

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing and wash before reuse.

Wash hands before breaks and at the end of work.

Avoid contact with the eyes and skin.

- · Breathing equipment: Not required.
- Protection of hands:



Protective gloves

#### · Material of gloves:

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material cannot be calculated in advance and has therefore to be checked prior to the application.

(Contd. on page 5)



OSHA HazCom Standard 29 CFR 1910.1200(g) revised in 2012 and GHS Rev 03.

Issue date 07/30/2021 Reviewed on 07/30/2021

### Trade Name: MagReSyn® Hydroxyl

· Penetration time of glove material:

The exact break-through time has to be determined and observed by the manufacturer of the protective gloves.

· Eye protection:



Tightly sealed goggles

· Limitation and supervision of exposure into the environment: None

## 9 Physical and Chemical Properties

· Information on basic physical and chemical properties

· General Information

· Appearance:

Form: Suspension Color: Black
Odor: Slight

· Odor threshold: Not determined. • pH-value: Not determined.

· Change in condition

Melting point/Melting range: Not determined.
 Flash point: 16 °C (60.8 °F)
 Flammability (solid, gaseous): Not applicable.
 Ignition temperature: Not applicable
 Decomposition temperature: Not determined.

· **Auto igniting:** Product is not self-igniting.

• Danger of explosion: Product is not explosive. However, formation of explosive air/vapor

mixtures are possible.

· Explosion limits:

**Lower:** ≥3.5 Vol % Upper: ≤15 Vol %

· Vapor pressure @ 20 °C (68 °F): ≤59 hPa (≤44.3 mm Hg)

· Density:

Relative density:

Vapor density:

Not determined.

Not determined.

Evaporation rate:

Not determined.

· Solubility in / Miscibility with:

Water: Miscible

· Partition coefficient (n-octanol/water): Not determined.

· Viscosity:

**Dynamic:** Not determined. **Kinematic:** Not determined.

· Solvent content:

Organic solvents: 20.0 %

(Contd. on page 6)



OSHA HazCom Standard 29 CFR 1910.1200(g) revised in 2012 and GHS Rev 03.

Issue date 07/30/2021 Reviewed on 07/30/2021

Trade Name: MagReSyn® Hydroxyl

 Water:
 78.0 %

 VOC content:
 20.00 %

 Solids content:
 2 %

• Other information: No further relevant information available.

## 10 Stability and Reactivity

- · Reactivity: No further relevant information available.
- · Chemical stability: Product is stable under normal conditions.
- · Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · Possibility of hazardous reactions: No dangerous reactions known.
- · Conditions to avoid: Heat, flame and ignition sources.
- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.

## 11 Toxicological Information

- · Information on toxicological effects:
- · Acute toxicity:

· LD/LC50 values that are relevant for classification:			
64-17-5 Et	64-17-5 Ethanol		
Oral	LD50	7,060 mg/kg (Rat) Remarks: Lungs, Thorax, or Respiration: Other changes. Carcinogenicity - Mouse - Oral Tumorigenic: Equivocal tumorigenic agent by RTECS criteria. Liver: Tumors. Blood: Lymphomas including Hodgkin's disease. Central nervous system depression, narcosis, Damage to the heart., To the best of our knowledge, the chemical, physical, and toxicological properties have not been thoroughly investigated. Heart - Irregularities - Based on Human Evidence Central nervous system - Breathing difficulties - Based on Human Evidence Stomach - Irregularities - Based on Human Evidence	
Inhalative	LC50/4 h	20,000 mg/l (Rat)	
	LC50/96 hours	12,900-15,300 mg/l (Trout)	

- · Primary irritant effect:
- · On the skin: Irritant to skin and mucous membranes.
- · On the eye: Irritating effect.
- Additional toxicological information:

The product shows the following dangers according to internally approved calculation methods for preparations:

Irritant

- · Carcinogenic categories:
- · IARC (International Agency for Research on Cancer):

The IARC (the International Agency for Research on Cancer) concluded that ethanol found alcoholic beverages to be Group 1 - Carcinogenic to humans. All other instances it is not consider carcinogenic.

64-17-5 Ethanol	1	
· NTP (National Toxicology Program):		
None of the ingredients are listed.		
(Contd. on page	ge 7)	



OSHA HazCom Standard 29 CFR 1910.1200(g) revised in 2012 and GHS Rev 03.

Issue date 07/30/2021 Reviewed on 07/30/2021

Trade Name: MagReSyn® Hydroxyl

· OSHA-Ca (Occupational Safety & Health Administration):

None of the ingredients are listed.

### 12 Ecological Information

- · Toxicity:
- · Aquatic toxicity:

#### 64-17-5 Ethanol

EC50 34,900 mg/l (Daphnia)

- Persistence and degradability: No further relevant information available.
- · Behavior in environmental systems:
- · Bioaccumulative potential: No further relevant information available.
- · Mobility in soil: No further relevant information available.
- Additional ecological information:
- · General notes:

Do not allow undiluted product or product that has not been neutralized to reach ground water, water course or sewage system.

- · Results of PBT and vPvB assessment:
- · **PBT**: Not applicable.
- · vPvB: Not applicable.
- Other adverse effects: No further relevant information available.

## 13 Disposal Considerations

- · Waste treatment methods
- · Recommendation:

Observe all federal, state and local environmental regulations when disposing of this material.

- · Uncleaned packaging
- Recommendation: Disposal must be made according to official regulations.

## 14 Transport Information

· UN-Number:

· **DOT** UN1170

· ADR/ADN, IMDG, IATA Limited Quantity

UN proper shipping name:

• **DOT** Ethanol mixture

· ADR/ADN UN1170 ETHANOL (ETHYL ALCOHOL) mixture

· **IMDG, IATA** Limited Quantity

· Transport hazard class(es):

· DOT



· *Class:* 3 Flammable liquids

(Contd. on page 8)



OSHA HazCom Standard 29 CFR 1910.1200(g) revised in 2012 and GHS Rev 03.

Issue date 07/30/2021 Reviewed on 07/30/2021

3

Trade Name: MagReSyn® Hydroxyl

· Label:

· ADR/ADN





Limited Quantity

· Class: 3 (F1) Flammable liquids

· Label:

· IMDG, IATA





Limited Quantity

· Class: 3 Flammable liquids

· Label: 3+ID8000

· Packing group:

· DOT, ADR/ADN, IMDG, IATA

· Environmental hazards: Not applicable.

· Special precautions for user: Warning: Flammable liquids

· Hazard identification number (Kemler code): 33

· EMS Number: F-E,S-D

· Stowage Category

Α

Not applicable.

· Transport in bulk according to Annex II of

MARPOL73/78 and the IBC Code:

· Transport/Additional information:

· DOT

Quantity limitations:

On passenger aircraft/rail: 5 L On cargo aircraft only: 60 L

· ADR/ADN

· Excepted quantities (EQ):

Limited quantities of dangerous goods packed in such limited quantities, meeting the provisions of

Chapter 3.4 DANGEROUS GOODS PACKED IN LIMITED QUANTITIES are NOT subject to any other provisions of ADR except the relevant provisions of:

(a) Part 1, Chapters 1.1, 1.2, 1.3, 1.4, 1.5, 1.6, 1.8, 1.9;

(b) Part 2;

(c) Part 3, Chapters 3.1, 3.2, 3.3 (except special provisions 61, 178, 181, 220, 274, 625, 633

and 650 (e));

(d) Part 4, paragraphs 4.1.1.1, 4.1.1.2, 4.1.1.4 to 4.1.1.8; (e) Part 5, 5.1.2.1(a) (i) and (b), 5.1.2.2, 5.1.2.3, 5.2.1.10,

(Contd. on page 9)



OSHA HazCom Standard 29 CFR 1910.1200(g) revised in 2012 and GHS Rev 03.

Issue date 07/30/2021 Reviewed on 07/30/2021

Trade Name: MagReSyn® Hydroxyl

5.4.2;

(f) Part 6, construction requirements of 6.1.4 and paragraphs

6.2.5.1 and 6.2.6.1 to 6.2.6.3;

(g) Part 7, Chapter 7.1 and 7.2.1, 7.2.2, 7.5.1 (except 7.5.1.4),

7.5.2.4, 7.5.7, 7.5.8 and 7.5.9;

(h) 8.6.3.3 and 8.6.4.

Code: E2

1L

Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml

· IMDG

· Limited quantities (LQ):

Excepted quantities (EQ): Code: E2

Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml

· IATA

· Remarks: Code: E1

**Excepted Quantity Shipment** 

Code Maximum Quantity (inner package) Maximum

Quantity per outer package

Not permitted E0 Not permitted E1 30g / 30ml 1Kg / 1L E2 30g / 30ml 500g / 500ml 30g / 30ml E3 300g / 300ml E4 1g / 1ml 500g / 500ml E5 1g / 1ml 300g / 300ml UN 1170 ETHANOL (ETHYL ALCOHOL) MIXTURE, 3, II

· UN "Model Regulation":

## 15 Regulatory Information

- Safety, health and environmental regulations/legislation specific for the substance or mixture: No further relevant information available.
- · SARA (Superfund Amendments and Reauthorization):

· Section 355 (extremely hazardous substances):	
None of the ingredients are listed.	
· Section 313 (Specific toxic chemical listings):	
None of the ingredients are listed.	
· TSCA (Toxic Substances Control Act):	
64-17-5 Ethanol	ACTIVE

· Hazardous Air Pollutants

None of the ingredients are listed.

7732-18-5 Water, distilled water, deionized water

- · California Proposition 65:
- · Chemicals known to cause cancer:

None of the ingredients are listed.

· Chemicals known to cause reproductive toxicity for females:

None of the ingredients are listed.

· Chemicals known to cause reproductive toxicity for males:

None of the ingredients are listed.

(Contd. on page 10)

**ACTIVE** 



OSHA HazCom Standard 29 CFR 1910.1200(g) revised in 2012 and GHS Rev 03.

Issue date 07/30/2021 Reviewed on 07/30/2021

#### Trade Name: MagReSyn® Hydroxyl

· Chemicals known to cause developmental toxicity:	
64-17-5 Ethanol	
New Jersey Right-to-Know List:	
64-17-5 Ethanol	
New Jersey Special Hazardous Substance List:	
64-17-5 Ethanol	CA, MU, TE, F3
· Pennsylvania Right-to-Know List:	
64-17-5 Ethanol	
Pennsylvania Special Hazardous Substance List:	
None of the ingredients are listed.	

· Carcinogenic categories:

· EPA (Environmental Protection Agency):

None of the ingredients are listed.

• TLV (Threshold Limit Value established by ACGIH):

64-17-5 Ethanol A3

· NIOSH-Ca (National Institute for Occupational Safety and Health):

None of the ingredients are listed.

· GHS label elements

The product is classified and labeled according to the Globally Harmonized System (GHS).

Hazard pictograms:





- · Signal word: Danger
- · Hazard-determining components of labeling:

Ethanol

· Hazard statements:

H225 Highly flammable liquid and vapor.

H319 Causes serious eye irritation.

H335 May cause respiratory irritation.

Precautionary statements:

P210 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

P240 Ground/bond container and receiving equipment.

P241 Use explosion-proof electrical/ventilating/lighting/equipment.

P242 Use only non-sparking tools.

P243 Take precautionary measures against static discharge.
P261 Avoid breathing dust/fume/gas/mist/vapors/spray.

P264 Wash thoroughly after handling.

P271 Use only outdoors or in a well-ventilated area.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P303+P361+P353 If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing.

P312 Call a poison center/doctor if you feel unwell.





OSHA HazCom Standard 29 CFR 1910.1200(g) revised in 2012 and GHS Rev 03.

Issue date 07/30/2021 Reviewed on 07/30/2021

#### Trade Name: MagReSyn® Hydroxyl

P337+P313 If eye irritation persists: Get medical advice/attention.

P370+P378 In case of fire: Use CO2, powder or water spray to extinguish. Store in a well-ventilated place. Keep container tightly closed.

P403+P235 Store in a well-ventilated place. Keep cool.

P405 Store locked up.

P501 Dispose of contents/container in accordance with local/regional/national/international

regulations.

#### · National regulations:

The product is not subject to be labelled according with the prevailing version of the regulations on hazardous substances.

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

#### 16 Other Information

The information and recommendations in this safety data sheet are, to the best of our knowledge, accurate as of the date of issue. Nothing herein shall be deemed to create warranty, expressed or implied, and shall not establish a legally valid contractual relationship. It is the responsibility of the user to determine applicability of this information and the suitability of the material or product for any particular purpose.

- · Contact:
- · Date of last revision/ revision number: 07/30/2021 / 2
- · Abbreviations and acronyms:

ADR: The European Agreement concerning the International Carriage of Dangerous Goods by Road

ADN: The European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

NIOSH: National Institute for Occupational Safety and Health

OSHA: Occupational Safety & Health Administration

TLV: Threshold Limit Value

PEL: Permissible Exposure Limit

REL: Recommended Exposure Limit

Flam. Liq. 2: Flammable liquids – Category 2

Eve Irrit. 2A: Serious eve damage/eve irritation – Category 2A

STOT SE 3: Specific target organ toxicity (single exposure) - Category 3

\* Data compared to the previous version altered.

SDS created by MSDS Authoring Services www.msdsauthoring.com +1-877-204-9106